

# GI #270 Dispersant

**APPLICATION:** GI #270 is a polymer-phosphonate formulation with excellent scale inhibition, deposit removal, and sludge conditioning properties. The action of GI #270 helps improve heat transfer rates and increases boiler efficiency.

**BENEFITS:** **WILL SAFELY REMOVE EXISTING DEPOSITS WHILE BOILER IS ON-LINE**  
**COMPATIBLE WITH OTHER BOILER WATER ADDITIVES**  
**NON-POLLUTING; ENVIRONMENTALLY ACCEPTABLE**

**PHYSICAL PROPERTIES:** Physical State: clear, straw-colored liquid  
Density: 8.84 lbs./gal.  
pH: 6.0 - 7.0  
Solubility: complete in water

**FEEDING:** Feed product on a continuous basis to the boiler by means of conventional mild steel pumping equipment. Compatible with other common boiler treatment products.

**DOSAGES:** Product dosage is dependent upon make up water quantities. Average dosage of GI #270 is 220 ppm.

**TESTING & CONTROL:** Product is monitored with the Model T2000 Phosphonate Test Kit. Maintain 10-15 ppm for maximum results.

**HANDLING & STORAGE:** Read label completely before use. See label for first aid instructions. Keep containers closed when not in use. Store containers in an area free of temperature extremes.

**PACKAGING:** Available in 5, 15, 30 and 55 gallon plastic containers.

**SHIPPING:** Product is shipped F.O.B. Birmingham, Al. unless otherwise specified.