

# GI #379 Closed System Treatment

**APPLICATION:** Guardian-IPCO #379 is a new generation corrosion inhibitor for use in closed hot and chilled water systems. This product will passivate all metals quickly and effectively by forming a tenacious film on the surfaces. The low order of toxicity of GI #379 makes it environmentally acceptable in those regions where effluent limitations are strict.

**BENEFITS:** EXCELLENT CORROSION INHIBITOR FOR ALL METALS.  
PRODUCT IS ENVIRONMENTALLY ACCEPTABLE.  
PRODUCT IS EASILY MONITORED WITH A QUICK TEST.

**PHYSICAL PROPERTIES:** Physical State: Clear, amber liquid  
Density: 9.39 lbs./gal.  
pH (neat): 9.0  
Solubility: Complete in water

**FEED RATES:** GI #379 should be shot fed to the system as needed to maintain treatment residuals.

**DOSAGES:** Average dosage of GI #379 is two quarts per 1000 gallons of system capacity.

**TESTING & CONTROL:** Treatment residuals are monitored with a T1805 Molybdenum Test Kit. Maintain 30 ppm molybdenum for maximum results.

**HANDLING & STORAGE:** Read label completely before use. See label for first aid instructions. Keep containers closed when not in use. Store containers in an area free of temperature extremes.

**PACKAGING:** Available in 5, 15, 30 and 55 gallon plastic containers.

**SHIPPING:** Product is shipped F.O.B. Birmingham, AL unless otherwise specified.

0595