

GI #570 Boiler Water Treatment

APPLICATION: GI #570 is a polymer-phosphonate formulation with excellent scale inhibition and sludge conditioning properties. GI #570 functions by crystal lattice distortion and antiprecipitation. It will also remove existing deposits, thus improving heat transfer and boiler efficiency.

BENEFITS: **MULTIFUNCTIONAL FORMULATION**
CAN BE USED AS A STAND-ALONE OR IN CONJUNCTION WITH
OTHER ADDITIVES
NON-POLLUTING; ENVIRONMENTALLY ACCEPTABLE

PHYSICAL PROPERTIES: Physical State: clear liquid
Density: 9.5 lbs./gal.
pH: 14.0
Solubility: complete in water

FEEDING: Feed product on a continuous basis to the boiler by means of conventional mild steel pumping equipment. Compatible with other common boiler treatment products.

DOSAGES: Product dosage is dependent upon make-up water quantities. Average dosage of GI #570 is 220 ppm.

TESTING & CONTROL: Product is monitored with the Model T2000 Phosphonate Test Kit. Maintain 10-15 ppm for maximum results.

HANDLING & STORAGE: Read label completely before use. See label for first aid instructions. Keep containers closed when not in use. Store containers in an area free of temperature extremes.

PACKAGING: Available in 5, 15, 30 and 55 gallon plastic containers.

SHIPPING: Product is shipped F.O.B. Birmingham, Al. unless otherwise specified.