

GI #622 Oxygen Scavenger

APPLICATION: GI #622 is a ready-to-use liquid oxygen scavenger which prevents internal boiler corrosion due to dissolved oxygen. Product reacts chemically with the dissolved oxygen to prevent pitting of boiler heating surfaces.

BENEFITS: PREVENTS THE PITTING OF BOILER INTERNALS.
REACTS WITH DISSOLVED OXYGEN INSTANTLY.
PRODUCT IS EASILY MONITORED WITH A QUICK TEST.

PHYSICAL PROPERTIES: Physical State: Clear to light amber liquid
Density: 10.0 lbs./gal.
pH of 1% Solution: 8.0
Solubility: Complete in water

FEEDING: For best results, it should be fed to the deaerator storage or feed water tank. Product is compatible with other boiler treatment products. Avoid excessive agitation when mixing.

DOSAGES: Dependent upon the temperature and dissolved oxygen content of the feed water. Average dosage is 2-4 ounces per 1000 gallons of make-up water.

TESTING & CONTROL: Treatment levels are monitored with the T1529 Sulfite Test Kit. Maintain 30 - 60 ppm sulfite in the boiler water.

HANDLING & STORAGE: Read label completely before use. See label for first aid instructions. Keep containers closed when not in use. Store containers in an area free of temperature extremes.

PACKAGING: Available in 5, 15, 30, and 55 gallon plastic containers.

SHIPPING: Product is shipped F.O.B. Birmingham, AL unless otherwise specified.

0595